



AUTOMATIC LIQUID SEED TREATER



Seed Treatment
IN THE FIELD
-When you want it!



Improve your Bottom Line with liquid seed treatment, **if it gets on the seed.** It can improve germination, reduce disease & maximize yields. However, **treated seed cannot be returned**, so why not treat seed in the field where you have control.



Pump Provides Even Flow and is powered by a 12Volt or 115V AC system. With the built-in internal bypass, pump life is extended. Easy seed cart mount or permanent mount with the universal mounting system.

Conveyor mounting bracket provides "open flow" to assure plug-free operation. It should be mounted at or above the jug mounting bracket to prevent siphoning.



Chemical Handling is supplied with a "dry-break" coupler to keep chemicals in the hose & off the operator as product containers are changed. The dip-tube has a cap, breather & mesh strainer to maintain product flow.

Metering Valve adjusts the flow rate for varied products & application rates. From 6oz to 60oz a minute can be applied, depending on the conveyor system requirements.



Hands-Free Operation takes place with the automatic on/off switch mounted in the discharge of the conveyor - when the conveyor runs - the seed treater runs! Shuts off when the conveyor is off. Convenient 3-way switch is provided at the operator platform. Connects to battery power with 50' wiring. Harness has weather tight plugs. Direct-wired models available.



LIQUID SEED TREATER OPERATION

Treater mounts directly to bulk seed wagons or at a permanent site. The bracket is set for a 2-1/2 gallon jug or easily modified for various size jugs (not furnished). Metering valve adjusts for the correct amount of product. Product is pumped directly into the conveyor through the open discharge fitting. The dry-break coupler, cap & dip tube are easily transferred between jugs.

SPECIFICATIONS

- **Automatic & Direct Models** - Complete with 50' wiring, automatic switch & weather tight plugs (automatic). Direct Model wires to 12Volt power on drill filler, air system, etc. 6' wire only.
- **Both Units include** - Mounting Bracket, Pump, Metering Valve, Dip-Tube with Strainer & Dry-Break Coupler.
- **Treater Capacity** - Mounting bracket holds 1 gal to 3 gal jugs (not included)
- **Metering Rate** - Rate will vary depending on product being dispensed. Contact factory for your application requirements.
- **Product Dispensed** -Most liquid seed treatments or inoculants. Review [product specification pages.](#)



ENVIROPAC, INC.

229 State Route 251 • Box 229 • Compton, IL 61318 • Phone (800) 752-1414 • Fax (815) 497-2300

www.enviropacinc.com